

Data sheet

Press Trim Module PT-220 for Konica Minolta Colour and Black & White Printers



Finishing solutions that add value to your business

KEY BENEFITS

- Optimises production quality
- Produces consistently flattened and trimmed booklets
- Easy to operate
- Automatic format change between two jobs
- Simple connection/installation behind the printer
- Interface to printer (with error signal)
- Adjustable trim size
- Patented design
- Durable knives
- Compatibility with Colour and Black & White production printers
- Optional SquareFold Module to create a square spine booklet

The **SDD PressTrim** Module is a face trimmer which trims the long edge of a booklet. Also, the system flattens the booklet by applying pressure to the spine. Finished booklets will have a superior, professional appearance and, as they lie flat, booklets are much easier to pack, stack and handle.

Obtain the look and feel of first class booklets! The optional SquareFold Module gives a booklet a perfectly flat finish with a square spine.



By printing on the spine it is possible to reproduce a professional magazine or book-like finish, which considerably enhances the booklet appearance.



With PT-220

Without PT-220



Optional Conveyor Belt Stacker CBS6060

GENERAL

System works from right to left
Paper input height: 200 mm (+ 20 mm)

COMPATIBILITY

Konica Minolta Printers equipped with
FS-532+SD-510 booklet finisher:

Colour devices:

bizhub PRO/PRESS C1060 / C1070 / C1070P
bizhub PRESS C1085 / C1100

B&W devices:

Bizhub PRESS 1052e / 1250e / 1250eP

OUTPUT OPTION

SF-204 SquareFold Module
CBS6060 Conveyor Belt Stacker 35cm + 15cm

PHYSICAL CHARACTERISTICS

	Length (mm)	Width (mm)	Height (mm)	Weight (kg)
PT-220	640	715	510	80
PT-220 packed	1200	800	850	115
SF-204	425	560	420	30
Konica Minolta Stacker	550	45	10	5

The PT-220 requires 400 mm of additional floor space at the front and rear side of the machine for installation, operation and maintenance.


TECHNICAL SPECIFICATIONS

Booklet size input

Booklet width range input 1 (x)	123 – 192mm
Booklet width range 2 (x)	208 – 254mm
Booklet width bypass (x)	108 -254mm
Booklet width range (z)	210-320mm

Booklet size output

Booklet width range input 1 (x)	121 – 167mm*
Booklet width range 2 (x)	183 – 229mm*
Booklet width bypass (x)	N.A.
*Face trim size (min-max): 2-25mm but within output specification	



Paper size

A4, A3, SRA4, SRA3, Letter, Legal, Ledger / Tabloid, etc.

Bypass

1 up to 20 sheets 80 g/m² (A5 – A4 booklet)

1 sheets 300 g/m² (SRA4 booklet)

Press / Trim capacity

2 up to 20 sheets 80 g/m² (A5 – A4 booklet)

2 up to 20 sheets 80 g/m² (SRA4 booklet)

2 up to 8 sheets 216 g/m² (SRA4 booklet)

Face trim size (min-max)

2-25mm (10mm is standard)

Paper Weight (min-max)

60 – 300 g/m²

Booklets size change

Automatic format change between two jobs

Output

55 cm long belt stacker

Productivity

up to 600 booklets per hour (printer speed maintained)

Power

100 - 240V / 7.3A 50 - 60Hz

Option: SquareFold Module

to ensure a professional square-spine finish: 3 pressure modes as well as bypass



SDD B.V. Print Finishing Solutions.

© March 2020 SDD B.V. Illustrations and specifications do not necessarily apply to the standard version of machines in all local markets. Technical specifications subject to change without prior notice. All products mentioned in this brochure are claimed as trademarks or registered trademarks of their respective companies.

DBCE-0314-0076-V012

SDDB.V.
Brinkerweg 5
8166 GD Emst
The Netherlands

Tel.: +31 (0)578 662 662

WEBSITE: WWW.SDDBV.COM
SALES: INFO@SDDBV.COM
SERVICE: SERVICE@SDDBV.COM